



Installation Quick Start Guide for WSBQ-1

Important Installation Instructions

1. Turn off water supply or ice maker to your refrigerator or water filtration system (refer to owners manual if needed).
2. Remove existing filter by turning filter counter clockwise one quarter turn.
3. Insert new filter into refrigerator or water treatment system by aligning tabs of filter with head assembly and inserting. Turn filter cartridge clockwise until it stops at about one quarter turn.
4. Turn water supply or ice maker back on from the shutoff valve on the cold water line.
5. Flush filter for five minutes to remove any trapped air.



Specifications

Flow Rate:	.5 gpm (1.89 lpm)
Operating Temperature:	33°-100°F (0.6°-38°C)
Operating Pressure:	25-100 psi (172-689 kPa)
Life:	6 Months or 1,500 gallons (5,678 liters)

For further questions or assistance please call (866) 218-8473.

Warning: To reduce the risk of property damage from water leakage, the filter bypass plug **MUST** be used when a filter replacement cartridge is not installed. For cold water applications only. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

Protect from freezing. REPLACE FILTER EVERY 6 MONTHS, OR IF BAD TASTE OR ODOR OCCUR.

Installation shall comply with applicable state and local regulations.

The risk associated with small parts can cause choking if swallowed.

Keep children away from small parts during the replacement of the water filter.

Aquamor, LLC, 42188 Rio Nedo, Temecula, CA

www.watersentinelfilters.com