



Installation Quick Start Guide for WSG-7

Important Installation Instructions

1. Turn off the water supply to your system.
2. Turn on faucet to drain the tank. This process may take a several minutes. It is recommended to reuse this water around your home to water your plants or garden.
3. Remove the prefilter and postfilter by rotating them to the left 1/3 of a turn.
Note: System should be sanitized when replacing the prefilter and postfilter. Refer to your system Owner's Manual for specific instructions.
4. Remove sanitary cap from new filter. Insert new filters into the manifold by turning to the right about 1/3 turn until the filter stops. The filters will rise up as they are turned. **DO NOT OVERTIGHTEN.**
5. Turn your water supply on to fill the system. This may take a few hours. Inspect the system for leaks.
6. To reset your timer, please refer to your system owner's manual for specific instructions.
7. Turn faucet onto flush and empty the filled storage tank once.

Micron Rating:	5 Micron
Flow Rate:	0.5 gpm (1.89 lpm)
Operating Temperature:	40-100°F (4.4°-38°C)
Min Operating Pressure:	40 psi (275 kPa)
Max Operating Pressure:	100 psi (689 kPa)
Life:	12 months or 3,800 gallons (14,384 liters)



This WSG-7 is Tested and Certified by NSF International against NSF/ANSI Standard 42 for the reduction of chlorine taste and odor.



This WSG-7 is Certified by IAPMO R&T against NSF/ANSI Standard 42 for the reduction of Chlorine taste and odor. Refer to Performance Data Sheet for complete list of claims.

For further questions or assistance please call (866) 218-8473.

Warning: To reduce the risk of property damage from water leakage, the filter bypass plug **MUST** be used when a filter replacement cartridge is not installed. For cold water applications only. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

Protect from freezing. **REPLACE FILTER EVERY 6 MONTHS, OR IF BAD TASTE OR ODOR OCCUR.**

Installation shall comply with applicable state and local regulations.

The risk associated with small parts can cause choking if swallowed.

Keep children away from small parts during the replacement of the water filter.

Aquamor, LLC, 42188 Rio Nedo, Temecula, CA

www.watersentinelfilters.com