



Installation Quick Start Guide for WSH-1

Important Installation Instructions

1. Turn off water supply. Locate existing filter and remove it by turning the filter cartridge counter clockwise a full $\frac{1}{4}$ turn.
2. To prevent water spillage on the filter tray, remove the filter by pulling it straight out.
3. Pull filter tray out and empty out any water to prevent leaking from the cartridge housing. Reinstall the tray.
4. Remove sanitary cap from new filter.
5. Insert the new filter into the housing head and rotate the filter clockwise $\frac{1}{4}$ turn or until it stops. Ensure filter is fully installed in refrigerator head a full $\frac{1}{4}$ turn. Turn on housing water supply.

Note: Please ensure the filter is fully installed as it is required to activate the internal water valve. If the filter isn't properly installed, you may experience a slow flow or a chattering noise. If this occurs, please uninstall and reinstall the filter ensuring the filter is fully installed.

6. Run approximately 2.5 gallons of water from the dispenser periodically to clear the system and to receive a good flow. If the water flow is slower than usual, please repeat Step 5. Note: Initial flow rate may be slower than expected. Full flow rate should be restored within 24-36 hours.
7. Inspect the filter for any noticeable leaks. If leaks are detected, please repeat Step 5.
8. To reset the filter monitor light, please refer to your refrigerator owner's manual for specific instructions.

Specifications

Flow Rate:	.5 gpm (1.89 lpm)
Operating Temperature:	33°-100°F (0.6°-38°C)
Operating Pressure:	30-100 psi (207-689 kPa)
Life:	6 Months or 300 gallons (1,136 liters)



This WSH-1 is Tested and Certified by NSF International against NSF/ANSI Standard 42 for the reduction of chlorine taste and odor.



This WSH-1 is Tested and Certified by IAPMO R&T against NSF/ANSI Standards 42, 53 & 372, for the reduction of Chlorine taste and odor, Lead, Cyst, VOC's, Mercury, Asbestos. Refer to Performance Data Sheet for complete list of claims.

For further questions or assistance please call (866) 218-8473.

Warning: To reduce the risk of property damage from water leakage, the filter bypass plug **MUST** be used when a filter replacement cartridge is not installed. For cold water applications only. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Protect from freezing. REPLACE FILTER EVERY 6 MONTHS, OR IF BAD TASTE OR ODOR OCCUR.

Systems Certified for cyst reduction may be used on disinfected waters that may contain filterable cysts.

Installation shall comply with applicable state and local regulations.

The risk associated with small parts can cause choking if swallowed.

Keep children away from small parts during the replacement of the water filter.

Aquamor, LLC, 42188 Rio Nedo, Temecula, CA

www.watersentinelfilters.com